

ACRYLIC EMBOSSING ADDITIVE™



DESCRIPTION

ACRYLIC EMBOSSING ADDITIVE™ is an acrylic latex admixture and primer developed for use with all DEPENDABLE trowel applied products. It is used in difficult adhesion circumstances, including over cushioned and non-cushioned embossed vinyl, vinyl tile and urethane wear layer vinyls. As an additive, it provides extraordinary flexibility and bond to virtually all substrates. As a primer, it has high resistance to oil based bleed through (such as cutback adhesive residues) and to water migration.

FEATURES AND BENEFITS

- Outstanding adhesion to most substrates
- Superior flexibility
- Mildewcide protection
- Resists water and bleed through
- ZERO VOC

PACKAGING

- 1 gallon bottle

PHYSICAL CHARACTERISTICS

Maximum coverage as a primer:
250 - 300 sq. ft./gallon

PREPARATION AND APPLICATION

SURFACE PREPARATION

Existing sheet vinyl floors shall be single layer, fully adhered and well bonded. Thoroughly clean all foreign matter such as dirt, grease, oil, wax or any other contaminates which may inhibit bond. While the floor is wet, use a cleaning pad and remove any remaining wax or dirt, while scuffing the surface. Rinse thoroughly with clean water and allow to dry.

Adhesive Residue

Using mechanical means, remove loose, brittle or thick/heavy accumulations to the minimal well bonded residue. Sweep or vacuum area.

CAUTION

Cutback adhesive may contain asbestos. Contact state or local authorities for proper removal and disposal procedures. Metal floors: remove rust, oil, dirt or any contaminates which may act as a bond breaker. Wash floor and allow to dry.

MIXING

After preparing the surface, use a clean mixing bucket and implements adding measured powder into measured liquid. Mix to a lump-free trowelable consistency. Follow printed mixing ratios of the appropriate Dependable Floor Underlayment product.

APPLICATION

Vinyl Floors

Using a flat, smooth steel trowel draw material across the pattern to be filled at angles to the pattern to ensure an even and complete fill. Before covering the vinyl or a second application allow the first application to DRY COMPLETELY, at least 2 hours.

PRIMING

Adhesive Residue

Using a paint roller or soft bristle broom, coat adhesive residue. Allow to nearly dry and become tacky. For best adhesion and flexibility, use Dependable's ACRYLIC EMBOSSING ADDITIVE™ with the desired Dependable floor underlayment product.

Metal

The use of ACRYLIC EMBOSSING ADDITIVE™ in place of water with the desired Dependable products increases adhesion properties and product flexibility. To assure a good chemical bond, metal surfaces may be primed with ACRYLIC EMBOSSING ADDITIVE™ using a paint roller or soft bristle brush. Allow primed area to nearly dry and become tacky.

KEEP FROM FREEZING

Freeze-thaw stable: If partially frozen allow to thaw at room temperature of 70°F. Stir. If smooth, then ACRYLIC EMBOSSING ADDITIVE™ should be safe to use.

24 HOUR EMERGENCY: CHEMTREC® 1-800-424-9300 NON-TOXIC and NON-FLAMMABLE

Keep container closed and keep away from children. May cause slight eye abrasion or irritation if spilled or rubbed in eyes. Flush thoroughly with water. If taken internally, call a physician. Technical Assistance: Visit our website: floorprep.com or call 1-800-227-3434. *It is always recommended that other branded products are tested with Dependable's products prior to use.*

LIMITED WARRANTY:

Dependable, LLC warrants to the initial purchaser only that the goods sold hereunder will be free from defects in material and workmanship and, except as otherwise set forth herein, will conform to the specifications provided. If any failure to meet this warranty appears within one year from the date of shipment of the goods, on the condition that Dependable, LLC. will correct any such failure by either replacing or repairing any defective goods, at Dependable, LLC's option.

The preceding paragraph sets forth the exclusive remedy for all claims based on failure of or defect in the goods sold hereunder, whether such failure or defect arises before or during the warranty period and whether a claim, however instituted, is based on contract, indemnity, warranty, tort (including negligence), strict liability or otherwise. The forgoing warranty is exclusive and is in lieu of all other warranties whether written, oral, implied or statutory.



P.O. Box 16307
Rocky River, OH 44116
info@dependable.us
www.floorprep.com



800 | 227 | 3434
P 440 | 333 | 1123
F 440 | 333 | 0070