



ANCHORING, PRIMERS, AND ADDITIVES

WHITE LATEX LIQUID®



DESCRIPTION

WHITE LATEX LIQUID® is formulated for use with DEPENDABLE WHITE SKIMCOAT™ Underlayment, it provides greater adhesion, water resistance, flexibility and mildewcide protection. It may be used as an additive with SKIMCRETE® XL and other DEPENDABLE trowelable products wherever a non re-emulsifiable latex primer or additive is required. It also may be used as a primer over textured or smooth metal surfaces, adhesive residues, or under leveling products used in exterior applications under certain circumstances in accordance with specific instructions.

FEATURES AND BENEFITS

- Outstanding adhesion to most substrates
- Mildewcide protection
- Outstanding flexural strength
- Effective additive with all DEPENDABLE powders

AS AN PRIMER

- Adhesive Residues
- Metal
- Porous or dusty surfaces (including GSL® and Gypcrete®)
- Other difficult bonding applications
- ZERO VOC

AS AN ADDITIVE

- Concrete to concrete bonding
- Thinsets and grouts
- Certain exterior applications (protected from UV)

PACKAGING

- 55 gallon container
- 5 gallon bucket with pour spout
- 1 gallon bottle

PHYSICAL CHARACTERISTICS

Maximum coverage as a primer:
250 - 300 sq. ft./gallon

PREPARATION AND APPLICATION

MIXING

After preparing the surface, use a clean mixing bucket and implements adding measured powder into measured liquid. Do not floor mix, use a piece of sheet vinyl or mixing bucket. Leftover residue can accelerate the chemical reaction and/or reduce working time of new mix. Mix to a lump-free trowelable consistency. Follow printed mixing ratios of the appropriate Dependable Floor Underlayment product.

PRIMING

Metal surfaces: Remove any rust or contaminants. Wash and allow to dry completely. Apply a brush-coat of WHITE LATEX LIQUID®. Allow to nearly dry and become tacky.

Porous Concrete and Gypsum Substrates

DEPENDABLE WHITE LATEX LIQUID® may be used to prime porous substrates for floor covering installation. Application rate will vary depending upon the substrate's porosity, but should be 150-250 SF/gallon. Allow to dry, usually 1-2 hours, and then begin adhesive application.

Underlayment Boards

The installer may wish to seal the joints, hammer-indent and any other "raw" spots with DEPENDABLE WHITE LATEX LIQUID®. This will keep the moisture in the patch material and/or adhesive from being drawn into the board, which may cause swelling and/or delamination.

KEEP FROM FREEZING

Freeze-thaw stable: If frozen, allow to thaw at room temperature of 70°F. Stir. If smooth, then latex should be safe to use.

NON-TOXIC NON-FLAMMABLE

Keep container closed when not in use. If taken internally, call physician and treat for ingestion of latex. KEEP OUT OF THE REACH OF CHILDREN.

24 HOUR EMERGENCY: CHEMTREC® 1-800-424-9300

NON-TOXIC and NON-FLAMMABLE

Keep container closed and keep away from children. May cause slight eye abrasion or irritation if spilled or rubbed in eyes. Flush thoroughly with water. If taken internally, call a physician. Technical Assistance: Visit our website: floorprep.com or call 1-800-227-3434.

It is always recommended that other branded products are tested with Dependable's products prior to use.

LIMITED WARRANTY:

Dependable, LLC warrants to the initial purchaser only that the goods sold hereunder will be free from defects in material and workmanship and, except as otherwise set forth herein, will conform to the specifications provided. If any failure to meet this warranty appears within one year from the date of shipment of the goods, on the condition that Dependable, LLC. will correct any such failure by either replacing or repairing any defective goods, at Dependable, LLC's option.

The preceding paragraph sets forth the exclusive remedy for all claims based on failure of or defect in the goods sold hereunder, whether such failure or defect arises before or during the warranty period and whether a claim, however instituted, is based on contract, indemnity, warranty, tort (including negligence), strict liability or otherwise. The forgoing warranty is exclusive and is in lieu of all other warranties whether written, oral, implied or statutory.



P.O. Box 16307
Rocky River, OH 44116
info@dependable.us
www.floorprep.com
800 | 227 | 3434
P 440 | 333 | 1123
F 440 | 333 | 0070

